

# 5



Docket No. 39872-177641

Patent

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In Re Application of )  
Applicant: Leslie JONES, ET AL. )  
Appln. No.: 10/050,825 )  
Filed: January 18, 2002 )  
For: "WORKMAN'S TOOL FOR ACCESSING )  
CAVITIES" )

Group Art No. 3724

Examiner:



26694

PATENT TRADEMARK OFFICE

PRELIMINARY AMENDMENT


Assistant Commissioner for Patents  
Washington, D.C. 20231

Sir:

Please substitute the enclosed Specification for the specification that was originally filed on January 18, 2002. The amendment to this Specification does not involve the addition of any new matter. A version showing the changes is attached hereto as Exhibit A.

Date: 3/26/2002

Respectfully submitted,

  
Andrew C. Aitken, #36,729

VENABLE

P.O. Box 34385

Washington, D.C. 20043-9998

Telephone: (202) 962-4800

Telefax: (202) 962-8300

## **Workman's Tool For Accessing Cavities**

### **BACKGROUND OF THE INVENTION**

[0001] The present invention is directed to a tool used for opening hollow core walls and ceilings to thereby allow access to the interior space of the wall or ceiling. The device includes a replaceable conventional pilot drill bit, a replaceable circular hole-cutting blade, (frequently referred to as a "hole saw,") a flange member and a series of rebate blades located at angular positions on the flange member.

[0002] A common manner for the construction interior walls in homes and office buildings is the attachment of gypsum board, also referred to as drywall and sheet rock, to structural members including studs, trusses and joists. Gypsum board is attached to upright studs to form walls and on the bottom of joists or trusses to form ceilings. These structural members are spaced at regular intervals and thereby this construction creates spaces between structural members. For example, in typical construction in the United States, studs used in walls are spaced at 16 inch intervals. When the framing stage of construction is complete, mechanical contractors, including plumbers, electricians, phone service technicians, and heating and air condition workers may install lines and equipment within the walls. These lines may include phone lines, cable television lines, gas lines, water and sewer conduits, vacuum lines for central vacuum and heating and air conditioning ducts and control lines. When the mechanical contractors have completed the installation, insulation is installed in the exterior walls and top floor ceiling areas. Next, gypsum boards are attached to the exposed studs and joists using glue, nails and/or screws. After the gypsum

boards have been installed, the surface is finished using tape and joint compound.

Finishing the gypsum board results in a smooth, continuous and seamless surface.

[0003]

Frequently, after the finishing work as described above has been completed, there is a need to install additional components within the finished walls. A homeowner or tenant may also have a need to access internal lines to make repairs. For example, it may be desirable to add insulation to walls that border the exterior of a completed structure. In order to introduce insulation to these spaces, holes must be temporarily created within each cavity between the structural members. In any event, the installation of new components within the walls and ceilings, or accessing existing components within the walls or ceiling requires cutting open the gypsum board to provide such access. Upon the completion of the job, the access hole must then be patched and the surface refinished. One conventional manner in which to patch holes requires cutting the access hole so that two adjacent structural members are revealed. Next a piece of drywall is cut to closely conform to the opening and attached to the adjacent structural members. One disadvantage with this technique is that it is difficult to apply the joint compound over and within the seam between the abutting edges without creating a bulge around the patch. While the bulge can be slowly tapered out to make the repair almost imperceptible, this procedure involves additional finishing work, and may require multiple applications of the joint compound. This technique also requires the creation of a fairly large access opening. An alternative repair technique involving taking a short piece of lumber and inserting the lumber through the access hole and then, attaching the lumber on the interior surface on opposite sides of the opening with a drywall screw so that the lumber spans the hole. A patch is then cut and attached to the lumber that spans the hole. This technique allows a smaller hole to be

created but still requires cutting a patch to closely conform to the hole and the problem of finishing the surface without a bulge is not avoided.

[0004] Another problem with cutting through these surfaces with conventional power tools is that the technician runs a risk of inadvertently cutting into the lines. The accidental rupture of a power line or water line can leave considerable remedial work to reinstate the walls or flooring.

[0005] Although there are a number of approaches to the problem of accessing interior spaces, including those not described in detail herein, there is a need for alternative and improved manners in which to access and patch hollow core walls and ceilings. Preferably this access and subsequent patch and replacement procedure can be performed with a minimal amount of time, effort and expense.

[0006] The present invention is directed to a tool and method of repair that allows the rapid access to hollow core walls and ceilings in a manner that enables the hole to be quickly formed and then repaired. According to the invention, a hole saw designed for use on a drill is provided with a rear flange attachment on which is provided a series of rebate blades. The hole saw is rotated and upon engagement with a substrate creates a hole through the substrate in a conventional manner. Continued axial movement of the device in the direction of the substrate causes the rotating rebate blades located outside the hole saw to then come into contact with the surface of the substrate. The rebate blades engage the surface, penetrate the substrate, and remove a portion of the substrate to form an annular cavity outside the through-hole that is formed by the hole saw. Further axial movement towards the substrate causes a flange to engage the surface of the substrate and prevents further axial movement. The device is then removed from the wall and a hole having an

annular cavity around the periphery of a through-hole is the resulting structure. The technician is then free to access the interior space and later provide a patch that can be seated in the annular cavity.

[0007] Fig. 1 is a top view in elevation of the flange portion of the invention.

[0008] Fig. 2 is a side view in elevation of the flange part of the invention also showing the pilot drill bit.

[0009] Fig. 3 is a bottom view in elevation of the flange part used in connection with the device according to the invention.

[0010] Fig. 4 is a top view in elevation of the hole saw used in connection with the present invention.

[0011] Fig. 5 is a side view in elevation of a hole saw used in connection with the invention.

[0012] Fig. 6 is a side view in elevation of the assembly of the device according to the invention that includes the flange, the hole saw and drill bit.

[0013] Fig. 7 is a side sectional view of the invention next to a hole that is formed through a substrate using the device according to the invention.

[0014] Fig. 8 is a side sectional view of a patch received in a hole in a substrate that was formed by the device according to the invention.

[0015] Fig. 9 is a side sectional view of an alternative patch received in a hole in a substrate formed by the device according to the invention.

[0016] Now referring to Fig 1, a top view of the flange member of the invention is depicted. At the center of the flange part 30 is hexagonal shank 10 that is comprised of metal and is designed to be received on the head of a conventional drill. The drill, which

may be either powered or manual, rotates the entire assembly including the flange member hold saw via the shank. Four through-holes 12a-12d are provided to received fasteners, such as screws, that engage and attach the hole saw through opposite holes 101a –101d that are provided through the rear end wall surface 22 of the hole saw 18 . Flange member 30 is domed shaped and serves to stop the device from penetrating the wall and prevents dust and debris from flying back into the vision of the user of the tool. Fig. 2, a side view of the flange assembly, further shows an axial passage 14 that receives a thumbscrew. The thumbscrew, not shown, engages pilot drill bit 16 that is received in a central cylindrical sleeve 18. Pilot bit 16 is the first part of the device that engages the surface into which a hole is to be formed using the device according to the invention and provides stability to the assembly when the blades of the hole saw engage the surface. As seen in Fig. 3, the bottom of flange member has four rebate blades 5a-5d attached thereon. Center sleeve 18 that receives the pilot drill bit is also depicted.

[00017] The cylindrical hole saw 18 according to the invention is depicted in Figs. 4 and 5. Fig 4 shows a top elevational view of hole saw 18 having sidewall 20 and endwall 22. Provided through endwall 22 are through holes 101a-101d that are used for the attachment of the hole saw 18 to the flange member 30 by an appropriate affixing means including screws or bolts and nuts. At the center of hole saw 18 is an opening or sleeve 24 through which the pilot drill bit is received. As seen in Fig. 5, hole saw 18 has a cutting surface 26 that is designed to engage and cut into the surface of a substrate. Lateral holes 28 and 29 are provided through the sidewall 20 in order to enable a user to remove a circular plug that is cut by the hole saw from the interior portion of the cylinder.

[00018] Fig 6a depicts the assembly of the components including the flange member 30, hole saw 18 and pilot drill bit 16. As best seen in Fig. 6b, the four rebate blades 5a-5d are axially positioned on the bottom side of the flange member 30 near the edge of the flanges and adjacent to hole saw 18. In the embodiment depicted in Fig. 6b the rebates blades are shown to have an “L shaped” profile wherein one surface is parallel with and is affixed to the bottom surface of flange member 30 and the other surface of the blade extends in an axial direction. The end of the rebate blade that extends in the axial direction is designed to engage the surface of the substrate. While in the specific embodiment depicted herein the rebate blades are affixed to the bottom surface of the flange 30, in an alternative embodiment of the invention the rebate blades may be attached to the outside of the hole saw. In yet a further contemplated embodiment the rebate blade consists of a second cylindrical hole saw directly adjacent, outside of, and concentric with an inner hole saw. The rebate blade or blades are formed of metal and are designed to cut into or abrade the surface of the substrate that is to be accessed and to create an annular cavity around the circumference of the through hole. The through hole is conventionally formed by the hole saw.

[00019] Fig. 7 depicts a sectional view of the invention directly above a hole that is formed by the tool wherein the shank 10 is engaged by drill head 50. In preferred embodiments, the axial length of the side wall of the circular hole saw from the flange members cutting surface is selected to be approximately the same as the thickness of the substrate to be accessed. By selecting a hole saw having a sidewall with an axial length that is approximately the same as the thickness of the substrate, the risk of accidentally cutting into materials or lines contained within the wall or ceiling is significantly reduced. In

operation, the pilot drill bit 16 first engages the surface of the substrate and penetrates the material. The pilot drill bit helps align the tool and maintains stability of the tool when the hole saw engages the surface of a substrate. Next, the cutting surface 26 of the hole saw engages the surface 65 of the substrate 80 and begins to abrade the surface in an annular ring. Continuing axial movement of the assembly causes the cutting surfaces 70 of the rebate blades 5a-5b to engage the surface of the substrate at a location just outside the engagement areas of the hole saw. The rebate blades 5a-5d, like the cutting surface 26 of the cylindrical hole saw 18, penetrate the surface 65 and abrade the material away. As the assembly continues to move in an axial direction, surface 61 of flange 30 engages the top surface 80 of substrate 80. The engagement of the flange to the top surface of the substrate prevents further axial movement of the assembly.

[00020] To repair the hole made by the device, a complementary disk shaped patch 120 is provided that closely conforms to the dimension of the hole. Referring now to Fig. 8 patch 120 may be made of a thin fiberboard having an axial dimension that closely conforms to the annular cavity 90 or, as shown in Fig 9, may have a stepped axial dimension wherein an outer annular region 152 of the patch has a thin axial dimension that is received in the annular cavity 90 and a thicker central core region 154 that is received in the through hole that was created by the hole saw. In either embodiment, the annular cavity serves to receive patch and secure it in place by providing a surface 92 wherein the patch may be seated. The patch is then further secured using adhesive and/or conventional joint compound.

[00021] In a preferred embodiment the invention, the device creates a hole large enough for the technician to inset his or her hand inside the cavity. Once the work is completed a pre-



manufactured hole cap or patch is affixed within the hole to reinstate the floor, ceiling or wall. In addition to gypsum or plaster board as described above, it is further contemplated that the invention may also be used to cut into chipboard or plywood flooring or other wood surfaces as well as materials made of synthetic resin or fiber. A variety of complementary patches may be provided that can be made of any materials that are intended to be engaged by the tool. Indeed, almost any surface may be penetrated by the device, including stone and tile, if the appropriate hole saw and rebate blades are used. In each of the contemplated uses, a patch can then be set in the hole that results from use of the tool.

[00022] It should be further appreciated that flange member does not have to rotate in order to practice the invention. For example, the blade may be affixed to rotating hole saw rather than the flange. In such an alternative embodiment the flange may still serve as a protective shield and as a manner in which to control the depth of penetration of the tool. In yet a further embodiment, a single hole saw having two concentric cutting surfaces may be used, with a flange portion, behind the second outer surface to serve as a stop.

[00023] Once again referring to Fig. 7, a first embodiment of a patch that can be used with the invention is merely a disk that can be inserted to the top portion of the hole created by the tool. In this embodiment, the patch is seated in the annular cavity created by the rebate blades and spans the hole created by the hole saw. The top surface 62 of the patch is within the same plane as the exterior surface 65 of the gypsum board. Fig. 9 shows an alternative patch having two axial dimensions. The outer edge region 152 has a dimension that approximates the depth of the annular cavity formed by the rebate blade and the central core region 154 extends into the through hole that was formed by the tool. The patch depicted in Fig. 7 has a dimension at the center core that is the same as the substrate. This

alternative patch may be used in situations where both sides of the may be finished and further gives additional structural strength to the wall.

[00024]

It should be appreciated that the dimensions of the hole saw, including the axial length and circumference, as well as the distance between cutting surface of the rebate blades and the cutting surface of the hole saw may be altered depending on the intended application. The axial dimensions of the sidewall of the hole saw from the flange to the cutting surface may be altered depending on the thickness of the substrate that is to be penetrated. It should also be appreciated that while the specific embodiment depicted herein shows four rebates blades, that any number of rebate blades could be used to achieve the objects of the invention. One should also recognize that although a circular flange is depicted to stop the forward movement of the device, other mechanism could be advantageously employed to ensure that the rebate blades penetrate a predetermined distance. For example, the blade itself could be provided with a flange extension that would allow a predetermined axial penetration.

[00025]

The description of the present invention has been presented for purposes of illustration and description, but is not intended to be exhaustive or limited to the invention in the form disclosed. Many modifications and variations will be apparent to those of ordinary skill in the art. The embodiment was chosen and described in order to best explain the principles of the invention, the practical application, and to enable others of ordinary skill in the art to understand the invention for various embodiments with various modifications as are suited to the particular use contemplated.

### **Abstract**

A tool assembly comprising a cylindrical hole saw having an annular cutting surface and at least one rebate blade positioned adjacent to the exterior sidewall of the hole saw having a cutting surface in a plane approximately parallel with the cutting surface of the hole saw and the rebate blade located a predetermined distance below the cutting surface of the cylindrical hole saw.

11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000 1001 1002 1003 1004 1005 1006 1007 1008 1009 1010 1011 1012 1013 1014 1015 1016 1017 1018 1019 1020 1021 1022 1023 1024 1025 1026 1027 1028 1029 1030 1031 1032 1033 1034 1035 1036 1037 1038 1039 1040 1041 1042 1043 1044 1045 1046 1047 1048 1049 1050 1051 1052 1053 1054 1055 1056 1057 1058 1059 1060 1061 1062 1063 1064 1065 1066 1067 1068 1069 1070 1071 1072 1073 1074 1075 1076 1077 1078 1079 1080 1081 1082 1083 1084 1085 1086 1087 1088 1089 1090 1091 1092 1093 1094 1095 1096 1097 1098 1099 1100 1101 1102 1103 1104 1105 1106 1107 1108 1109 1110 1111 1112 1113 1114 1115 1116 1117 1118 1119 1120 1121 1122 1123 1124 1125 1126 1127 1128 1129 1130 1131 1132 1133 1134 1135 1136 1137 1138 1139 1140 1141 1142 1143 1144 1145 1146 1147 1148 1149 1150 1151 1152 1153 1154 1155 1156 1157 1158 1159 1160 1161 1162 1163 1164 1165 1166 1167 1168 1169 1170 1171 1172 1173 1174 1175 1176 1177 1178 1179 1180 1181 1182 1183 1184 1185 1186 1187 1188 1189 1190 1191 1192 1193 1194 1195 1196 1197 1198 1199 1200 1201 1202 1203 1204 1205 1206 1207 1208 1209 1210 1211 1212 1213 1214 1215 1216 1217 1218 1219 1220 1221 1222 1223 1224 1225 1226 1227 1228 1229 1230 1231 1232 1233 1234 1235 1236 1237 1238 1239 1240 1241 1242 1243 1244 1245 1246 1247 1248 1249 1250 1251 1252 1253 1254 1255 1256 1257 1258 1259 1260 1261 1262 1263 1264 1265 1266 1267 1268 1269 1270 1271 1272 1273 1274 1275 1276 1277 1278 1279 1280 1281 1282 1283 1284 1285 1286 1287 1288 1289 1290 1291 1292 1293 1294 1295 1296 1297 1298 1299 1300 1301 1302 1303 1304 1305 1306 1307 1308 1309 1310 1311 1312 1313 1314 1315 1316 1317 1318 1319 1320 1321 1322 1323 1324 1325 1326 1327 1328 1329 1330 1331 1332 1333 1334 1335 1336 1337 1338 1339 1340 1341 1342 1343 1344 1345 1346 1347 1348 1349 1350 1351 1352 1353 1354 1355 1356 1357 1358 1359 1360 1361 1362 1363 1364 1365 1366 1367 1368 1369 1370 1371 1372 1373 1374 1375 1376 1377 1378 1379 1380 1381 1382 1383 1384 1385 1386 1387 1388 1389 1390 1391 1392 1393 1394 1395 1396 1397 1398 1399 1400 1401 1402 1403 1404 1405 1406 1407 1408 1409 1410 1411 1412 1413 1414 1415 1416 1417 1418 1419 1420 1421 1422 1423 1424 1425 1426 1427 1428 1429 1430 1431 1432 1433 1434 1435 1436 1437 1438 1439 1440 1441 1442 1443 1444 1445 1446 1447 1448 1449 1450 1451 1452 1453 1454 1455 1456 1457 1458 1459 1460 1461 1462 1463 1464 1465 1466 1467 1468 1469 1470 1471 1472 1473 1474 1475 1476 1477 1478 1479 1480 1481 1482 1483 1484 1485 1486 1487 1488 1489 1490 1491 1492 1493 1494 1495 1496 1497 1498 1499 1500 1501 1502 1503 1504 1505 1506 1507 1508 1509 1510 1511 1512 1513 1514 1515 1516 1517 1518 1519 1520 1521 1522 1523 1524 1525 1526 1527 1528 1529 1530 1531 1532 1533 1534 1535 1536 1537 1538 1539 1540 1541 1542 1543 1544 1545 1546 1547 1548 1549 1550 1551 1552 1553 1554 1555 1556 1557 1558 1559 1560 1561 1562 1563 1564 1565 1566 1567 1568 1569 1570 1571 1572 1573 1574 1575 1576 1577 1578 1579 1580 1581 1582 1583 1584 1585 1586 1587 1588 1589 1590 1591 1592 1593 1594 1595 1596 1597 1598 1599 1600 1601 1602 1603 1604 1605 1606 1607 1608 1609 1610 1611 1612 1613 1614 1615 1616 1617 1618 1619 1620 1621 1622 1623 1624 1625 1626 1627 1628 1629 1630 1631 1632 1633 1634 1635 1636 1637 1638 1639 1640 1641 1642 1643 1644 1645 1646 1647 1648 1649 1650 1651 1652 1653 1654 1655 1656 1657 1658 1659 1660 1661 1662 1663 1664 1665 1666 1667 1668 1669 1670 1671 1672 1673 1674 1675 1676 1677 1678 1679 1680 1681 1682 1683 1684 1685 1686 1687 1688 1689 1690 1691 1692 1693 1694 1695 1696 1697 1698 1699 1700 1701 1702 1703 1704 1705 1706 1707 1708 1709 1710 1711 1712 1713 1714 1715 1716 1717 1718 1719 1720 1721 1722 1723 1724 1725 1726 1727 1728 1729 1730 1731 1732 1733 1734 1735 1736 1737 1738 1739 1740 1741 1742 1743 1744 1745 1746 1747 1748 1749 1750 1751 1752 1753 1754 1755 1756 1757 1758 1759 1760 1761 1762 1763 1764 1765 1766 1767 1768 1769 1770 1771 1772 1773 1774 1775 1776 1777 1778 1779 1780 1781 1782 1783 1784 1785 1786 1787 1788 1789 1790 1791 1792 1793 1794 1795 1796 1797 1798 1799 1800 1801 1802 1803 1804 1805 1806 1807 1808 1809 1810 1811 1812 1813 1814 1815 1816 1817 1818 1819 1820 1821 1822 1823 1824 1825 1826 1827 1828 1829 1830 1831 1832 1833 1834 1835 1836 1837 1838 1839 1840 1841 1842 1843 1844 1845 1846 1847 1848 1849 1850 1851 1852 1853 1854 1855 1856 1857 1858 1859 1860 1861 1862 1863 1864 1865 1866 1867 1868 1869 1870 1871 1872 1873 1874 1875 1876 1877 1878 1879 1880 1881 1882 1883 1884 1885 1886 1887 1888 1889 1890 1891 1892 1893 1894 1895 1896 1897 1898 1899 1900 1901 1902 1903 1904 1905 1906 1907 1908 1909 1910 1911 1912 1913 1914 1915 1916 1917 1918 1919 1920 1921 1922 1923 1924 1925 1926 1927 1928 1929 1930 1931 1932 1933 1934 1935 1936 1937 1938 1939 1940 1941 1942 1943 1944 1945 1946 1947 1948 1949 1950 1951 1952 1953 1954 1955 1956 1957 1958 1959 1960 1961 1962 1963 1964 1965 1966 1967 1968 1969 1970 1971 1972 1973 1974 1975 1976 1977 1978 1979 1980 1981 1982 1983 1984 1985 1986 1987 1988 1989 1990 1991 1992 1993 1994 1995 1996 1997 1998 1999 2000 2001 2002 2003 2004 2005 2006 2007 2008 2009 2010 2011 2012 2013 2014 2015 2016 2017 2018 2019 2020 2021 2022 2023 2024 2025 2026 2027 2028 2029 2030 2031 2032 2033 2034 2035 2036 2037 2038 2039 2040 2041 2042 2043 2044 2045 2046 2047 2048 2049 2050 2051 2052 2053 2054 2055 2056 2057 2058 2059 2060 2061 2062 2063 2064 2065 2066 2067 2068 2069 2070 2071 2072 2073 2074 2075 2076 2077 2078 2079 2080 2081 2082 2083 2084 2085 2086 2087 2088 2089 2090 2091 2092 2093 2094 2095 2096 2097 2098 2099 2100 2101 2102 2103 2104 2105 2106 2107 2108 2109 2110 2111 2112 2113 2114 2115 2116 2117 2118 2119 2120 2121 2122 2123 2124 2125 2126 2127 2128 2129 2130 2131 2132 2133 2134 2135 2136 2137 2138 2139 2140 2141 2142 2143 2144 2145 2146 2147 2148 2149 2150 2151 2152 2153 2154 2155 2156 2157 2158 2159 2160 2161 2162 2163 2164 2165 2166 2167 2168 2169 2170 2171 2172 2173 2174 2175 2176 2177 2178 2179 2180 2181 2182 2183 2184 2185 2186 2187 2188 2189 2190 2191 2192 2193 2194 2195 2196 2197 2198 2199 2200 2201 2202 2203 2204 2205 2206 2207 2208 2209 2210 2211 2212 2213 2214 2215 2216 2217 2218 2219 2220 2221 2222 2223 2224 2225 2226 2227 2228 2229 2230 2231 2232 2233 2234 2235 2236 2237 2238 2239 2240 2241 2242 2243 2244 2245 2246 2247 2248 2249 2250 2251 2252 2253 2254 2255 2256 2257 2258 2259 2260 2261 2262 2263 2264 2265 2266 2267 2268 2269 2270 2271 2272 2273 2274 2275 2276 2277 2278 2279 2280 2281 2282 2283 2284 2285 2286 2287 2288 2289 2290 2291 2292 2293 2294 2295 2296 2297 2298 2299 2300 2301 2302 2303 2304 2305 2306 2307 2308 2309 2310 2311 2312 2313 2314 2315 2316 2317 2318 2319 2320 2321 2322 2323 2324 2325 2326 2327 2328 2329 2330 2331 2332 2333 2334 2335 2336 2337 2338 2339 2340 2341 2342 2343 2344 2345 2346 2347 2348 2349 2350 2351 2352 2353 2354 2355 2356 2357 2358 2359 2360 2361 2362 2363 2364 2365 2366 2367 2368 2369 2370 2371 2372 2373 2374 2375 2376 2377 2378 2379 2380 2381 2382 2383 2384 2385 2386 2387 2388 2389 2390 2391 2392 2393 2394 2395 2396 2397 2398 2399 2400 2401 2402 2403 2404 2405 2406 2407 2408 2409 2410 2411 2412 2413 2414 2415 2416 2417 2418 2419 2420 2421 2422 2423 2424 2425 2426 2427 2428 2429 2430 2431 2432 2433 2434 2435 2436 2437 2438 2439 2440 2441 2442 2443 2444 2445 2446 2447 2448 2449 2450 2451 2452 2453 2454 2455 2456 2457 2458 2459 2460 2461 2462 2463 2464 2465 2466 2467 2468 2469 2470 2471 2472 2473 2474 2475 2476 2477 2478 2479 2480 2481 2482 2483 2484 2485 2486 2487 2488 2489 2490 2491 2492 2493 2494 2495 2496 2497 2498 2499 2500 2501 2502 2503 2504 2505 2506 2507 2508 2509 2510 2511 2512 2513 2514 2515 2516 2517 2518 2519 2520 2521 2522 2523 2524 2525 2526 2527 2528 2529 2530 2531 2532 2533 2534 2535 2536 2537 2538 2539 2540 2541 2542 2543 2544 2545 2546 2547 2548 2549 2550 2551 2552 2553 2554 2555 2556 2557 2558 2559 2560 2561 2562 2563 2564 2565 2566 2567 2568 2569 2570 2571 2572 2573 2574 2575 2576 2577 2578 2579 2580 2581 2582 2583 2584 2585 2586 2587 2588 2589 2590 2591 2592 2593 2594 2595 2596 2597 2598 2599 2600 2601 2602 2603 2604 2605 2606 2607 2608 2609 2610 2611 2612 2613 2614 2615 2616 2617 2618 2619 2620 2621 2622 2623 2624 2625 2626 2627 2628 2629 2630 2631 2632 2633 2634 2635 2636 2637 2638 2639 2640 2641 2642 2643 2644 2645 2646 2647 2648 2649 2650 2651 2652 2653 2654 2655 2656 2657 2658 2659 2660 2661 2662 2663 2664 2665 2666 2667 2668 2669

## Workman's Tool For Accessing Cavities

### BACKGROUND OF THE INVENTION

**[0001]** The present invention is directed to a tool used for opening hollow core walls and ceilings to thereby allow access to the interior space of the wall or ceiling. The device includes a replaceable conventional pilot drill bit, a replaceable circular hole-cutting blade, (frequently referred to as a "hole saw,"), a flange member and a series of rebate blades located at angular positions on the flange member.

**[0002]** A common manner for the construction interior walls in homes and office buildings is the attachment of gypsum board, also referred to as drywall and sheet rock, to structural members including studs, trusses and joists. Gypsum board is attached to upright studs to form walls and on the bottom of joists or trusses to form ceilings. These structural members are spaced at regular intervals and thereby this construction creates spaces between structural members. For example, in typical construction in the United States, studs used in walls are spaced at 16 inch intervals. When the framing stage of construction is complete, mechanical contractors, including plumbers, electricians, phone service technicians, and heating and air condition workers may install lines and equipment within the walls. These lines may include phone lines, cable television lines, gas lines, water and sewer conduits, vacuum lines for central vacuum and heating and air conditioning ducts and control lines. When the mechanical contractors have completed the installation, insulation is installed in the exterior walls and top floor ceiling areas. Next, gypsum boards are attached to the exposed studs and joists using glue, nails and or screws. After

the gypsum boards have been installed, the surface is finished using tape and joint compound. Finishing the gypsum board results in a smooth, continuous and seamless surface.

[0003] Frequently, after the finishing work as described above has been completed, there is a need to install additional components within the finished walls. A homeowner or tenant may also have a need to access internal lines to make repairs. For example, it may be desirable to add insulation to walls that border the exterior of a completed structure. In order to introduce insulation to these spaces, holes must be temporarily created within each cavity:— between the structural members. In any event, the installation of new components within the walls and ceilings, or accessing existing components within the walls, or ceiling requires cutting open the wall gypsum board to provide such access. Upon the ~~completing~~ completion of the job, the access hole must then be patched and the surface refinished. One conventional manner in which to patch holes requires cutting the access hole so that two adjacent structural members are revealed. ~~Then~~ Next a piece of drywall is cut to closely conform to the opening and attached to the adjacent structural members. One disadvantage with this technique is that it is difficult to apply the joint compound over and within the seam between the abutting edges without creating a bulge around the patch. While the bulge can be slowly tapered out to make the repair almost imperceptible, this procedure involves additional finishing work, and may require multiple applications of the joint compound. This technique also requires the creation of a fairly large access opening. An alternative repair technique involving taking a short piece of lumber and inserting the lumber through

the access hole and then, attaching the lumber on the interior surface on opposite sides of the opening with a drywall screw so that the lumber spans the hole. A patch is then cut and attached to the lumber that spans the hole. This technique allows a smaller hole to be created but still requires cutting a patch to closely conform to the hole and the problem of finishing the surface without a bulge is not avoided.

**[0004]** Another problem with cutting through these surfaces with conventional power tools is that the technician runs a risk of inadvertently cutting into the lines. The accidental rupture of a power line or water line can leave considerable remedial work to reinstate the walls or flooring.

**[0005]** Although there are a number of approaches to the problem of accessing interior spaces, including those not described in detail herein, there is a need for alternative and improved manners in which to access and patch hollow core structure walls and ceilings. Preferably this access and subsequent patch and replacement procedure can be performed with a minimal amount of time, effort and expense.

#### **SUMMARY OF THE INVENTION**

**[0006]** The present invention is directed to a tool and method of repair that allows the rapid access to hollow core walls and ceilings in a manner that enable ~~enables~~ the hole to be quickly formed and then repaired. According to the invention, a hole saw designed for use on a drill, is provided with a rear flange attachment on which is ~~provide~~ provided a series of rebate blades. The hole saw is rotated and upon engagement with a substrate creates a hole through the surface of a sheet-substrate in a conventional manner ~~by penetrating substrate~~. Continued axial movement of the device in the direction of the substrate causes the rotating rebate blades located

outside the hole saw to then come into contact with the surface of the substrate. The rebate blades engage the surface, penetrate the substrate, and remove a portion of the substrate to form an annular cavity outside ~~at the through-hole~~ that is formed by the hole saw. Further axial movement towards the substrate causes a flange to engage the surface of the substrate and prevents further axial movement. The device is then removed from the wall and a hole having an annular cavity around the periphery of a through-hole is the resulting structure. The technician is then free to access the interior space and later provide a patch that can be seated in the annular cavity.

#### **BRIEF DESCRIPTION OF THE DRAWINGS**

**[0007]** Fig. 1 is a top view in elevation of the flange portion of the invention.

**[0008]** Fig. 2 is a side view in elevation of the flange part of the invention also showing the pilot drill bit.

**[0009]** Fig. 3 is a bottom view in elevation of the flange part used in connection with the device according to the invention.

**[00010]** Fig. 4 is a top view in elevation of the hole saw used in connection with the present invention.

**[00011]** Fig. 5 is a side view in elevation of a hole saw used in connection with the invention.

**[00012]** Fig. 6 is a side view in elevation of the assembly of the device according to the invention that includes the flange, the hole saw and drill bit.

**[00013]** ~~Fig. 6b is a perspective view in elevation of the hole saw, drill bit and flange assembly.~~

[00014] Fig. 7 is a side sectional view of the invention next to a hole that is formed through a substrate using the device according to the invention.

[00015] Fig. 8 is a side sectional view of a patch received in a hole in a substrate that was formed by the device according to the invention.

[00016] Fig. 9 is a side sectional view of an alternative patch received in a hole in a substrate formed by the device according to the invention.

#### ~~DETAILED DESCRIPTION OF THE SPECIFIC EMBODIMENTS~~

[00017] Now referring to Fig 1, a top view of the flange ~~portion~~member of the invention is depicted. ~~At~~ the center of the flange part 30 is hexagonal shank 10 that is comprised of metal and is designed to be received on the head of a conventional drill. The drill, which may be either powered or manual, rotates the entire assembly including the flange member hold saw via the shank. Four through-holes 12 a-12d are provided to received fasteners, such as screws, that engage and attach the hole saw through opposite holes 101a-101d. ~~Holes 101a-101b~~that are provided through the rear ~~end~~wall ~~end~~ 22 wall surface 22 of the hole saw 18 . Flange member 30 is domed shaped and serves to stop the device from penetrating the wall and prevents dust and debris from flying back into the vision of the user of the tool. Fig. 2, a side view of the flange assembly, further shows an axial passage 14 that receives a thumbscrew. The thumbscrew, not shown, engages pilot drill bit 16 that is received in a central cylindrical sleeve 18. Pilot bit 16 is the first part of the device that engages the surface into which a hole is to be formed using the device according to the invention and provides stability to the assembly when the blades of the hole saw engage the surface. ~~As~~ seen in Fig. 3, the bottom of flange



member has four rebate blades 5a-5d ~~attach~~attached thereon. Center sleeve 18 that ~~received~~receives the pilot drill bit is also depicted.

**[00018]** The cylindrical hole saw 18 according to the invention is depicted in Figs. 4 and 5. Fig 4 shows a top elevational view of hole saw 18 having sidewall 20 and ~~end wall~~endwall 22. Provided through ~~end wall~~endwall 22 are through holes 101a-101d that are used for the attachment of the hole saw 18 to the flange member 30 by an appropriate affixing means including screws or bolts and nuts. At the center of hole saw 18 is an opening or sleeve 24 through which the pilot drill bit is received. As seen in Fig. 5, hole saw 18 has a cutting surface 26 that is designed to engage and cut into the surface of a substrate. Lateral holes 28 and 29 are provided through the sidewall 20 in order to enable a user to remove a circular plug that is cut by the hole saw from the interior ~~portion of the~~portion of the cylinder.

**[00019]** Fig 6a depicts the assembly of the components including the flange member 30, hole saw 18 and pilot drill bit 16. As best seen in Fig. 6b, the four rebate blades 5a-5d are axially positioned on the bottom side of the flange member 30 near the edge of the flanges and adjacent to hole saw 18. In the embodiment depicted in Fig. 6b the rebates blades are shown to have an “L shaped” profile wherein one surface is parallel with and is affixed to the bottom surface of flange member 30 and the other surface of the blade extends in an axial direction. The end of the rebate blade that extends in the axial direction is designed to engage the surface of the substrate. While in the specific embodiment depicted herein, the rebate blades are affixed to the bottom surface of the flange 30, in an alternative embodiment of the invention the rebate blades may be attached to the outside of the

hole saw. In yet a further contemplated embodiment the rebate blade consists of a second cylindrical hole saw directly adjacent, outside of, and concentric with an inner hole saw. The rebate blade or blades are formed of metal and are designed to cut into or abrade the surface of the substrate that is to be accessed and to create an annular cavity around the circumference of the through hole. The ~~trough~~through hole is conventionally formed by the hole saw.

**[00020]** Fig. 7 depicts a sectional view of the invention directly above a hole that is formed by the tool wherein the shank 10 is engaged by drill head 50. In preferred embodiments, the axial length of the side wall of the circular hole saw from the flange members cutting surface is selected to be approximately the same as the thickness of the substrate to be accessed. By selecting a hole saw having a sidewall with an axial length that is approximately the same as the thickness of the substrate, the risk of accidentally cutting into materials or lines contained within the wall or ceiling is significantly reduced. In operation, the pilot drill bit 16 first engages the surface of the substrate and penetrates the material. The pilot drill bit helps align the tool and maintains stability of the tool when the hole saw engages the surface of a substrate. Next, the cutting surface 26 of the hole saw engages the surface 65 of the substrate 80 and begins to abrade the surface in an annular ring. Continuing axial movement of the assembly causes the cutting surfaces 70 of the rebate blades 5a-5b to engage the surface of the substrate at a location just outside the engagement areas of the hole saw. The rebate blades 5a-5d, like the cutting surface 26 of the cylindrical hole saw 18, penetrate the surface 65 and ~~abrades~~abrade the material away. As the assembly continues to move in an axial direction, surface 61 of flange

30 engages the top surface 80 of substrate 80. The engagement of the flange to the top surface of the substrate prevents further axial movement of the assembly.

[00021] To repair the hole made by the device, a complementary disk shaped patch 120 is provided that closely conforms to the dimension of the hole. Referring now to Fig. 8 patch 120 may be made of a thin fiberboard having an axial dimension that closely conforms to the annular cavity 90 or, as shown in Fig 9, may have a stepped axial dimension wherein an outer annular region 152 of the patch has a thin axial dimension that is received in the annular cavity 90 and a thicker central core region 154 that is received in the ~~through~~through hole that was created by the hole saw. In ~~any~~either event~~embodiment~~, the annular cavity serves to receive patch and secure it in place by providing a surface 92 wherein the patch may be seated. The patch is then is further secured using adhesive and/or conventional joint compound.

[00022] In a preferred embodiment the invention, the device creates a hole large enough for the technician to inset his or her hand inside the cavity. Once the work is completed a pre-manufactured hole cap or patch is affixed within the hole to reinstate the floor, ceiling or wall. In addition to gypsum or plaster board as described above, it is further contemplated that the invention may also be used to ~~used to~~ cut into chipboard or plywood flooring or other wood surfaces as well as materials made of synthetic resin or fiber. A variety of complementary patches may be provided that can be made of any materials that are intended to be engaged by the tool. Indeed, almost any surface may be penetrated by the device, including stone and tile, ~~in the event that~~if the appropriate hole saw and rebate blades are used. In

each of the contemplated uses, a patch can then be set in the hole that results from use of the tool.

**[00023]** It should be further appreciated that flange member does not have to rotate in order to practice the invention. For example, the blade may be affixed to rotating hole saw rather than the flange. In such an alternative embodiment the flange may still serve as a protective shield and as a manner in which to control the depth of penetration of the tool. In yet a further embodiment, a single hole saw having two concentric cutting surfaces may be used, with a flange portion, behind the second outer surface to serve as a stop.

**[00024]** Once again referring to Fig. 7, a first embodiment of a patch that can be used with the invention is merely a disk that can be inserted to the top portion of the hole created by the tool. In this embodiment, the patch is seated in the annular cavity created by the rebate blades and spans the hole created by the hole saw. The top surface 62 of the patch is within the same plane as the exterior surface 65 of the gypsum board. Fig. 9 shows an alternative patch having two axial dimensions. The outer edge region 152 has a dimension that approximates the depth of the annular cavity formed by the rebate blade and the central core region 154 extends into the through hole that was formed by the tool. The patch depicted in Fig. 7 has a dimension at the center core that is the same as the substrate. This alternative patch may be used in situations where both sides of the may be finished and further, and gives additional structural strength to the wall.

**[00025]** It should be appreciated that the dimensions of the hole saw, including the axial length and circumference, as well as the distance between cutting surface

of the rebate blades and the cutting surface of the hole saw may be altered depending on the intended application. The axial dimensions of the sidewall of the hole saw from the flange to the cutting surface may be altered depending on the thickness of the substrate that is to be penetrated. It should also be appreciated that while the specific embodiment depicted herein shows four rebates blades, that any number of rebate blades could be used to achieve the objects of the invention. One should also recognize that although a circular flange is depicted to stop the forward movement of the device, other mechanism could be advantageously employed to ensure that the rebate blades penetrate a predetermined distance. For example, the blade itself could be provided with a flange extension that would allow a predetermined axial penetration.

[00026] The description of the present invention has been presented for purposes of illustration and description, but is not intended to be exhaustive or limited to the invention in the form disclosed. Many modifications and variations will be apparent to those of ordinary skill in the art. The embodiment was chosen and described in order to best explain the principles ~~of the~~ of the invention, the practical application, and to enable others of ordinary skill in the art to understand the invention for various embodiments with various modifications as are suited to the particular use contemplated.

**We claim:**

1. A tool assembly comprising a cylindrical hole saw having an annular cutting surface and at least one rebate blade, said rebate blade positioned adjacent to the exterior sidewall of said hole saw and said rebate blade having a cutting surface in a plane approximately parallel with the cutting surface of said hole saw and said rebate blade located a predetermined distance below said cutting surface of said cylindrical hole saw.
2. The tool recited in claim 1 further comprising a flange member, said flange member located on said hole saw on an end opposite said cutting surface and said flange member having a diameter larger than the diameter of said hole saw, wherein when said flange member engages the surface of a by said holes saw, further axial movement is prevented.
3. The tool assembly recited in claim 2 wherein said rebate blade is attached to said flange member.
4. The tool assembly as recited in claim 3 wherein said flange member receives a plurality of rebate blades.
5. The tool assembly as recited in claim 4 wherein said rebate blades are positioned at angular positioned around said flange.
6. The tool assembly as recited in claim 1 further comprising a pilot drill bit, wherein said drill bit is received in a sleeve in the center of said cylindrical hole saw.
7. The tool assembly recited in claim 1 further comprising a shank, said shank adapted for reception in the head or chuck of a drill.

8. A method of providing an access hole ~~through~~ through a substrate comprising, engaging the surface of said substrate with a cylindrical hole saw, boring through said substrate with said hole saw, allowing rebate blade to comprising.

9. A method of accessing an interior space comprising the steps of using the assembly recited in claim to form an access opening in a surface of a substrate, said access opening having an annular through passage and an annular cavity around the exterior of said passage, accessing said interior space, and next inserting in a patch in said hole, said patch received and seated in said annular cavity.

10. An access and repair kit comprising the device recited in claim 1 and a plurality of patches, said patches having a radial dimension approximately the same as the distance from the center of the cylindrical hole saw to the cutting surface of said rebate blade that is the most distant from the center of said hole saw center, and said patches having a uniform axial dimension approximately equal to the distance that said rebate blade extends in an axial dimension from said flange member.

~~from of the equal to that and the edge of the rebate blade and having a uniform axial dimension approximately equal to the distance of the equal to the accessing~~

11. The tool assembly as recited in claim 1 wherein said rebate blades are detachable and replaceable from the hole saw component of the assembly.

~~12.~~ 12. The tool assembly as recited in claim 1 wherein said cylindrical hole saw is detachable and replaceable from said rebate blade component of the tool.

~~13.~~ 13. The tool assembly as recited in claim 4 wherein said pilot drill bit is detachable and replaceable from the rebate blade component of the tool.

14. A tool assembly comprising a first cutting means to cut a first annular groove into the surface of a substrate, and a second cutting means to cut an annular track adjacent to and outside said first groove, said first cutting means being positioned at a leading edge of said assembly and second means located at a second axial position behind said first cutting means, and engine means to allow for the rotation of said first and second cutting means around a central axis, and stop means wherein said stop means engage said surface outside of said second track and said stop means allows for the predetermined limited movement in an axial direction of said assembly into said substrate.